



Bed Assembly

To assemble a bed you will need an assistant, a screwdriver and a light hammer. Stand up the headboard and tailboard. Line up the *click in fittings* on both sides with the *click in fittings* on the headboard and tailboard. Push in by hand.

If the side rails need to be tapped down with a light hammer, make a pad to place on top of the side rails (to protect the finish). A flat stick wrapped in a cloth is suitable.

When the *click in fittings* are aligned, you will see there is a small hole in the centre of the fittings. **Lock the fittings together with the screw provided.**

To fit centre rail for Double, Queen and King beds, line up the *click in fittings* and push rail into place. Tap down with a hammer if necessary.

Unroll the slats with the **tape down**, onto the side rails. Secure slats to the side rails with the screws provided. For Double, Queen and King beds, secure slats to centre rail with the screws provided.

Bunks

Assemble both beds as above. Place a (provided) steel connecting rod in each hole in the bottom bunk bedposts. Lift the top bunk above the bottom bunk and place down onto the connecting rods.

Fit safety rail and ladder as follows:

1. Click horizontal safety rail into fitting on top bunk headboard.
2. Click ladder into other end of safety rail
3. Bolt ladder to top bunk and bottom bunk side rails. Use stainless steel bolts provided, insert into predrilled holes.
4. Secure safety rail fittings with lock screw provided (there is a small hole in the centre of the click in fittings).

When the bunks are converted in to 2 beds, fix the provided capping pieces into the bottom bunk bedposts with P.V.A. or temporarily fix in with a paper wedge.

